

Technical Specification



VorzAMP pure II ™ is true to its name, in being an amplifier that is the dream of the Purist. This new high performance, ultra-low distortion, high fidelity amplifier with its 3 gain settings is designed to capture the whole spectrum of earphones devices, from the sensitive and precision IEMs to the power hungry professional Headphones.

Through our handcrafted assembly, stringent testing and audio matching procedures our boutique company is able to ensure high hardware quality. VorzAMP pure II ™ is a completely analogue system, possess strong dynamics, clean sound and crisp vocal, deep black background with excellent instrument separation and placing – it is indeed the unique boutique amplifier for the Purist.





Impedances:

 $\begin{array}{cc} \text{Input impedance} & 13 \text{ k}\Omega \\ \text{Output Impedance} & <0.1\Omega \\ \text{Headphone impedance} & 8 \ \Omega \text{ - }600 \ \Omega \\ \end{array}$

Audio:

BW	15Hz - 100kHz		±0.2 dB
SNR	>110 dB		32 Ω; 0.1W
THD + N	<0.0008 %		0Hz-20kHz; 0.2W
			battery operated
Slew rate	2000V/μs		
DC stop filter	Yes		
Gain	0,89	-1 dB	Gain: Low
	2,5	8 dB	Gain: Middle
	5,4	15 dB	Gain: High



Technical Specification



Output:

Maximum Voltage RMS 3,2 Vrms

Maximum Voltage swing 9 V

Maximum output Current 250 mA x2

Output power RMS 250,0 mW x2 Load of 8 Ω

 $\begin{array}{ccccc} 500,0 & \text{mW x2} & & \text{Load of } 16 \ \Omega \\ 568,9 & \text{mW x2} & & \text{Load of } 18 \ \Omega \\ 320.0 & \text{mW x2} & & \text{Load of } 32 \ \Omega \\ 160.0 & \text{mW x2} & & \text{Load of } 64 \ \Omega \\ 34.1 & \text{mW x2} & & \text{Load of } 300 \ \Omega \end{array}$

17.1 mW x2

Load of 600Ω

Battery:

Play time 10 hours

Charging time 3 hours

Micro USB charge current ≥900mA ≥USB2.0

Charge cycles ≥500

Product Casing:

Total weight 130g

case coating Extra tough powder coated
Shielding Full grounded aluminum case
Color Ivory Pearl / Signal Black

Size 83 x 66 x 18 [mm³] Slim design

Components:

RoHS Yes

Resistors Precision metal film

Signal path Capacitors None

Pad Gold plated

Connects Silver-Gold Solder

Included:

Audio Equipment: VorzAMPpure II™ With Battery

VorzKABEL 3.5mm Audio

jack

USB Charger 5V, 1A USB cable Micro USB

Documentation: User-Guide

Technical Specification

Certification: Warranty Card
Others: Protective pouch
Box Size: 17.5 x 15.5 x 7.5 [cm³]

Box weight: 450 g Fully loaded